Online Hose Datasheet

Creation Date:

150

167

10



Cert. acc. ISO 9001

MEINERT-Flex

MULTI-PURPOSE-Hose - Oil suction and delivery hose with high flexibility and helix wire



Multi purpose oil suction and delivery hose for mineral oil and Hose: grease products (Hydrocarbons with up to 60% aromatic rate) Mandrel built multi purpose oil hose for suction and pressure applications suitable for minerl oil and grease products as well as **Application** hydrocarbons with an aromatic rate up to 60% and emulsions, gas, compressed air, water and low concentrated acid and alkaline solutions Construction Black smooth Perbunan rubber -NBR Tube: Suitable for fuel with a aromatic rate up to max, 60% and low concentrated chemicals Reinforcement: Textile plies, steel helix wire embedded, antistatic wire embedded Black, fabric impressed, conductive corrugated Neoprene rubber - CR, Cover: resitant to abrasion, oil, fuel, ozone and weather! Meinert-flex Perbunan - NBR - PN 10 Marking: **Technical Data** -20 ° C from **Working Temperature:** short term peaks up to +100°C +80 ° C up to **Dimensions Bending** WP BP **Vacuum** ID OD Weight Length radius Comment [mm] [mm] [bar] [bar] [%] [g/m] [m] [mm] 27 19 10 <- 3x 80 80 500 40 25 33 10 <- 3x 80 100 600 40 30 38 10 <- 3x 80 120 700 40 * on stock 10 <- 3x 80 1000 40 * on stock 40 48 160 50 60 10 <- 3x 80 200 1800 40 70 10 240 2300 40 60 <- 3x 80 87 80 75 10 <- 3x 300 3000 40 103 10 <- 3x 80 360 3800 40 90 100 113 10 80 400 4300 40 <- 3x 140 125 10 <- 3x 80 525 6100 20/40

Other sizes and pressures available on request! Sections possible!
Technical data, structures and polymers are subjekt to change without prior notice! Not subject to updating service!

750

8900

20/40

Meinert GmbH · Schnackenburgallee 151 · 22525 Hamburg · Germany · Tel: +49 40 555 865-0 · Fax: +49 40 555 865-99 · Email: info@meinert-hamburg.de

Errors excepted!

60

<- 3x